

## Features

- Specifically designed for use with constant pressure (variable speed) and jet style pumping systems where treatment of extreme levels of iron, manganese and sulfur gas is required
- Disinfection properties with added contact time for iron, manganese and sulfur bacteria control
- Includes reliable peristaltic chemical feed pump package for self-priming operation
- Signature Series 2™ control valve with built in contact flow meter for precise metering of hydrogen peroxide & compressor control
- Legacy View Bluetooth enabled control valve for advanced diagnostics and simplified setup
- Advanced electronic technology and simple programming
- Adjustable cycle times
- High backwash flow capability
- 3/4" FNPT stainless steel bypass
- 1" FNPT stainless steel bypass (optional)
- Features Enpress® Vortech™ distributor plate
- Poly wound HydroxR™ and mineral tank
- Simple 9 volt battery back-up keeps electronic meter active and will motor control valve to shut off position if in regeneration during power failure



General Specifications	UTP15VS-S2	UTP20VS-S2	UTP25VS-S2	UTP30VS-S2
Filter Media Type	SmartBlend™			
Filter Media Capacity (cu ft)	1.5	2.0	2.5	3.0
Mineral Tank (Vortech™)	10 x 54	12 x 52	13 x 54	13 x 65
Service Flow Rate - Continuous (gpm)	5	6	8	9
Service Flow Rate - Intermittent (gpm)	7	8	10	11
Backwash Flow Rate (gpm)	5.0	6.0	7.0	7.0
Gallons Used / Backwash	100	120	140	140
Space Required HydroxR™ Tank	21 x 21 x 71	21 x 21 x 71	21 x 21 x 71	21 x 21 x 71
Space Required Filter Tank	10 x 10 x 62	12 x 12 x 60	13 x 13 x 62	13 x 13 x 73
Space Required Feed Pump System	17 x 17 x 28.5	17 x 17 x 28.5	17 x 17 x 28.5	17 x 17 x 28.5
Approximate Shipping Weight (lbs)	175	246	280	321

Note: Caution should always be used in sizing filters! Always choose a unit by first satisfying the *Backwash requirement*. Use of a flow control in the Service Line is highly recommended. Consult the factory or your field sales person with questions.