



Features

- Perfect for Filtering and Softening in ONE system
- Signature Series 2™ timeclock or meter initiated controls
- Legacy View Bluetooth enabled control valve for advanced diagnostics and simplified setup
- Features Enpress® Vortech™ mid-plate technology
- Adjustable cycle times
- Calendar Day Override (metered versions only)
- 3/4" FNPT stainless steel bypass
- 1" FNPT stainless steel bypass(optional)
- Poly wound mineral tank with high flow 1" distribution tube
- High capacity cation exchange resin
- Dome fill opening for ease of service
- High flow brine safety float assembly, overflow fitting, grid plate, and brine well
- Simple 9 volt battery back-up keeps electronic meter active and will motor control valve to shut off position if in regeneration during power failure

General Specifications	Two Tanks in One			
	TSF32-10D-S2	MSF32-10D-S2	TSF48-15D-S2	MSF48-15D-S2
Regeneration Type	Timed	Metered	Timed	Metered
Select Filter Media	1 cu ft	1 cu ft	1.5 cu ft	1.5 cu ft
Softening Capacity	32,000	32,000	48,000	48,000
**Salt Used / Regeneration (lbs)	15.0	15.0	24.0	24.0
Service Flow Rate (gpm)*	5	5	8	8
Intermittent Flow Rate (gpm)	7	7	10	10
Backwash Flow Rate (gpm)	5	5	7	7
Mineral Tank Size (inches)	10 x 65	10 x 65	13 x 65	13 x 65
Gallons Used / Backwash	130	130	170	170
Space Required	18 x 28 x 73	18 x 28 x 73	18 x 31 x 73	18 x 31 x 73
Approximate Shipping Weight (lbs)	126	126	182	182

* The pressure drop does not exceed 15.0 psi at the service flow rate.

** Factory Salt Setting; 15lbs./cuft.