


Revolutionary Features

- Air is injected into the top of the tank converting ferrous iron to ferric iron after untreated water has passed through the control valve preventing the control valve from fouling with iron
- Signature 3™ Control Valve
- Legacy View Bluetooth enabled control valve for advanced diagnostics and simplified set up
- Simple 9 volt battery back-up keeps electronic meter active and will motor control valve to shut off position if in regeneration during power failure
- Includes meter to provide water usage history
- Air draw cycle can be initiated without a backwash cycle saving 1000's of gallons of water annually
- The control valve slowly releases compressed air charge prior to backwash cycle eliminating the explosive blast that can dislodge the drain line
- Adjustable cycle times
- Proprietary two valve bypass with 1" MNPT Connections
- High Flow 1" distributor
- Catalytic Carbon & KDF cubes for Sulfur Reduction
- Top cap fill opening for ease of service
- Compatible with any type of well pump system



| General Specifications | SK15S | SK25S |
|--|--------------|--------------|
| Filtration Media Capacity (CU. FT.) | 1.5 cu. ft. | 2.5 cu. ft. |
| KDF Cubes | 1.5 lbs | 2.5 lbs |
| Mineral Tank | 10 X 54 | 13 X 54 |
| Service Flow Rate - Continuous (GPM) | 5 | 8 |
| Service Flow Rate - Intermittent (GPM) | 7 | 10 |
| Backwash Flow Rate (GPM) | 5.0 | 7.0 |
| Gallons Used / Backwash | 106 | 146 |
| Space Required (D x W x H inches) | 10 X 21 X 61 | 13 X 24 X 61 |
| Approximate Shipping Weight | 160 | 236 |