



Features

- Designed to treat the full flow of the home (up to 40 gpm)
- Simple Filter changes without tools
- No backwash wastewater
- Compact - 8"D x 42"H
- Commercial size available - 2" in/out (up to 135 gpm)
- NSF Standard 61 Listed
- 150psi working pressure

Cartridge Tanks

General Specifications	CTF8	CTF8-HF
Color	Black	Black
Inlet / Outlet (in.)	1.25"	2"
Maximum Flow Rate (gpm)	40	135
Cartridge Dimensions (in.)	8" D x 42" H	8" D x 42" H

Carbon Block Filters for Taste/Order Removal & Sediment

General Specifications	CT-20-CB (Blue)	CT-03-CB-AMINE	CT-ACP (Red-High Flow Only)
Micron Rating	20	3	5
Treatment Description	Chlorine / Sediment	Chlorine / Sediment	Chlorine / Sediment
Max Flow Rate / psi drop	60 / 15	55 / 20	150 / 4

Filters for Sediment Removal

General Specifications	CT-105 (Orange)	CT-2005 SWMB (Yellow)	CT-2010 SWMB (Orange)	CT-P1A (Red-High Flow Only)	CT-P5 (Red-High Flow Only)	CT-P20 (Red-High Flow Only)
Micron Rating	10 x 5	20 x 5	20 x 10	Absolute 1	5	20
Treatment Description	Sediment	Sediment	Sediment	Sed / Cyst	Sediment	Sediment
Max Flow Rate / psi drop	60 / 20	60 / 20	50 / 3	100 / 15	125 / 10	135 / 7