



Features

- Eliminates Hardness (Calcium & Magnesium)
- Reduces Iron / Manganese stains and taste
- Signature 2™ Series Control Valve
- Legacy View Bluetooth enabled control valve for advanced diagnostics and simplified setup
- Adjustable cycle times
- Calendar Day Override (metered versions only)
- 3/4" FNPT stainless steel bypass
- 1" FNPT stainless steel bypass (optional)
- Poly wound mineral tank with high flow 1" distribution tube
- "V" units feature Enpress® Vortech™ distributor plate for exceptional backwashing capability
- High Flow brine safety float assembly, overflow fitting, grid plate, and brine well
- Standard brine tank size 18" X 33" with space saving 14" x 14" and oversized 18" x 40" brine tanks available
- Simple 9 volt battery back-up keeps electronic meter active and will motor control valve to shut off position if in regeneration during power failure

General Specifications	TS24-S2 MS24-S2 TS24V-S2 MS24V-S2	TS32-S2 MS32-S2 TS32V-S2 MS32V-S2	TS48-S2 MS48-S2 TS48V-S2 MS48V-S2	TS64-S2 MS64-S2 TS64V-S2 MS64V-S2	TS96V-S2* MS96V-S2*
Grains Capacity - Regeneration / Lbs Salt Used**	24,000 / 12 20,250 / 7.5 15,000 / 4.5	32,000 / 15 27,000 / 9 20,000 / 6	48,000 / 24 40,500 / 15 30,000 / 9	64,000 / 30 54,000 / 18 40,000 / 12	96,000 / 45 81,000 / 27 60,000 / 18
Maximum Raw Water Hardness (grains)	50	75	100	100	100
Maximum Clear Iron / Manganese	3	5	5	5	5
Exchange Resin (cu ft per tank)	.75	1.0	1.5	2.0	3.0
Mineral Tanks (polyglass)	8 x 44	9 x 48	10 x 54	12 x 52	13 x 65
Brine Tank (polyethylene w grid & safety)	18 x 33	18 x 33	18 x 33	18 x 33	18 x 40
Service Flow Rate (gpm per active tank)*	8.0	10.0	11.0	12.0	14.0
Backwash Flow Rate (gpm)	1.5	2.0	2.4	3.5	
Gallons Used / Regeneration	79	90	101	140	
Backwash Flow Rate (gpm) Vortech (V) Units	1.2	1.5	2.0	2.4	3.0
Gallons Used / Regeneration Vortech (V) Units	69	78	90	117	126
Space Required	18x26x53	18x27x 56	18x28x 62	18x30x 60	18x32x 74
Approximate Shipping Weight (lbs)	88	100	133	164	285

*96 Series only available in Vortech Units

* The pressure drop does not exceed 15.0 psi at the service flow rate.

** Factory Salt Settings: - 9lbs./cuft.