

| General Specifications | CM24-S4 | CM32-S4 | CM48-S4 |
|---|--------------|--------------|--------------|
| Grains Capacity - Regeneration / Lbs Salt Used* | 20,000 / 7.5 | 27,000 / 9 | 40,000 / 15 |
| Maximum Raw Water Hardness (grains) | 50 | 75 | 100 |
| Maximum Clear Iron / Manganese | 3 | 5 | 5 |
| Exchange Resin (cu. ft. per tank) | .75 | 1.0 | 1.5 |
| Mineral Tank Size | 9 x 35 | 9 x 35 | 12 x 35 |
| Service Flow Rate** (GPM) | 8.0 | 10.0 | 11.0 |
| Backwash Flow Rate (GPM) | 2.0 | 2.0 | 2.4 |
| Gallons Used / Regeneration | 86 | 88 | 90 |
| Space Required (D x W x H) | 23 x 14 x 45 | 23 x 14 x 45 | 23 x 14 x 45 |
| Approximate Shipping Weight (lbs) | 88 | 100 | 133 |



System Features

- Eliminates Hardness (Calcium & Magnesium)
- Available with **S4™** control valve technology and Signature 3
- Legacy View Bluetooth enabled control valve for advanced diagnostics and simplified setup
- Slide Cover design for easy access to salt compartment
- Simple 9 volt battery back-up keeps electronic meter active and will motor control valve to shut off position in regeneration during power failure
- On-demand meter provides detailed water usage data and history
- Adjustable Cycle Times
- Calendar Day Override
- Proprietary two valve bypass with 1" MNPT Connections
- High Flow 1" distributor
- Treated Water Refill with pre-brine option
- High flow brine safety float assembly overflow fitting and brine well

* Factory Salt Setting: 9 lbs / cu. ft.

** The pressure drop does not exceed 15.0 psi at the service flow rate.